

## **REMARKS**

In view of the above amendments and the following remarks, reconsideration and further examination are respectfully requested.

### **I. Interview**

The Applicant would like to thank Examiner Kayrish for granting and conducting a telephone interview on July 23, 2008 in connection with the above-identified application. During the interview the Applicants' proposed claims (represented as claims 44 and 45) were reviewed by the Examiner. In addition, during the interview, the Examiner suggested that Applicants amend proposed claim 44 to recite that "the land track and the groove track are adjacent to one another," in order to overcome the prior art rejections. In addition, the Examiner agreed that the proposed features relating to the polarity of the wobble signal also distinguish from the prior art of record.

Based on the above-mentioned interview, new independent claim 44 has been drafted to include the distinguishing limitations discussed during the interview in order to overcome the references cited by the Examiner in the Office Action of April 29, 2008.

### **II. Objections**

The specification and abstract have been reviewed and revised to improve their English grammar as well as address the informalities identified on page 2 of the Office Action. Specifically, as requested in the objection, page 1, line 19 now states "a rewritable optical disk," rather than "an rewritable optical disk." Furthermore, page 16, lines 18-24, as identified in the

objection have been reworded to read properly. Therefore, withdrawal of these objections respectfully requested.

The amendments to the specification and abstract have been incorporated into a substitute specification and abstract. Attached are two versions of the substitute specification and abstract, a marked-up version showing the revisions, as well as a clean version. No new matter has been added.

In accordance with Examiner's request, the title of the invention has been amended. The invention is now titled "INFORMATION RECORDING MEDIUM AND INFORMATION REPRODUCING METHOD."

### **III. 35 U.S.C. § 103(a) Rejection of Claims 21, 23, 25 and 40-43**

Claims 21, 23, 25 and 40-43 were rejected under 35 U.S.C. § 103(a) as being unpatentable over Lee (U.S. 6,847, 594) in view of Eguchi et al. (U.S. 2001/005088).

Claims 1-43 have been cancelled without prejudice or disclaimer of the subject matter contained therein and replaced by new claims 44 and 45. As mentioned above, claims 44 and 45 have been drafted to distinguish the present invention from the above-mentioned references. Thus, for the reasons discussed below, this rejection is clearly inapplicable to claims 44 and 45 for the reasons discussed below.

Independent claim 44 recites an information recording medium for having information recorded thereto according to a wobble formed thereon and according to one of a groove-recording system and a land-recording system. Further, according to claim 44, the information recording medium includes (1) a land track configured to have information recorded thereto and

a groove track located adjacent to the land track and closer to the incident laser beam than the land track, and configured to have information recorded thereto. In addition, according to claim 44, when information is recorded to a recording track (being one of the land track and the groove track) (2) the information is recorded according to a wobble formed on the recording track. Moreover, claim 44 recites that (3) when the information is recorded onto the recording track of the information recording medium according to the groove-recording system, a physical direction toward which the wobble formed on the recording track starts a first wobble deviation is a mirror reverse of a situation when the information is recorded onto the recording track of the information recording medium according to the land-recording system, and when the information is recorded onto the recording track of the information recording medium according to the land-recording system, the physical direction toward which the wobble formed on the recording track starts the first wobble deviation is a mirror reverse of a situation when the information is recorded onto the recording track of the information recording medium according to the groove-recording system. Finally, claim 44 recites that (4) a polarity of a wobble signal representing the wobble formed on the recording track of the information recording medium according to the groove-recording system is identical to a polarity of a wobble signal representing the wobble formed on the recording track of the information recording medium according to the land-recording system. Lee and Eguchi fail to disclose or suggest above-mentioned distinguishing features (1)-(4), as recited in claim 44.

Rather, Lee teaches a medium having (i) wobbled groove tracks which are out of phase by “ $\pi$ ” and wobbled land tracks which are in phase, or (ii) wobbled land tracks which are out of phase by “ $\pi$ ” and wobbled groove tracks which are in phase, based upon a type of recording (see

col. 5, lines 11-40, and fig. 5).

Thus, in view of the above, it is clear that, although Lee teaches various wobble tracks being in phase and out of phase based on a type of recording, Lee still fails to disclose or suggest, as required by claim 44, a land track and groove track that is adjacent to the land track, wherein:

- (i) when the information is recorded onto the recording track of the information recording medium according to the groove-recording system, a physical direction toward which the wobble formed on the recording track starts a first wobble deviation is a mirror reverse of a situation when the information is recorded onto the recording track of the information recording medium according to the land-recording system;
- (ii) when the information is recorded onto the recording track of the information recording medium according to the land-recording system, the physical direction toward which the wobble formed on the recording track starts the first wobble deviation is a mirror reverse of a situation when the information is recorded onto the recording track of the information recording medium according to the groove-recording system; and
- (iii) a polarity of a wobble signal representing the wobble formed on the recording track of the information recording medium according to the groove-recording system is identical to a polarity of a wobble signal representing the wobble formed on the recording track of the information recording medium according to the land-recording system.

In addition, it is also noted that Eguchi merely teaches a wobble deviation towards and inner side or an outer side of a recording medium (see figs. 5 and 6, and paragraphs [0049]-[0051]). However, Eguchi fails to disclose or suggest the above-mentioned distinguishing features (1)-(4) which are, as acknowledged by the Examiner, lacking from Lee.

Moreover, regarding combining the features of Lee and Eguchi, it is noted that Eguchi requires that the width of the grooves and lands are substantially constant and that the neighboring grooves coincide in phase with each other. However, on the other hand, Lee teaches that the width of the groove is not constant and the neighboring grooves are out of phase. Thus, it is respectfully submitted that the requirement of Eguchi (that the widths of the grooves/lands are constant) is incompatible with the invention of Lee, since Lee teaches that the widths of the grooves are not constant.

Therefore, because of the above-mentioned distinctions it is believed clear that claim 44 and claim 45 that depends therefrom would not have been obvious or result from any combination of Lee and Eguchi.

Furthermore, there is no disclosure or suggestion in Lee and/or Eguchi or elsewhere in the prior art of record which would have caused a person of ordinary skill in the art to modify Lee and/or Eguchi to obtain the invention of independent claim 44. Accordingly, it is respectfully submitted that independent claim 44 and claim 45 that depends therefrom are clearly allowable over the prior art of record.

#### **IV. 35 U.S.C. § 103(a) Rejection of Claim 22**

Claim 22 was rejected under 35 U.S.C. § 103(a) as being unpatentable over the

combination of Lee, Eguchi and Maeda et al (U.S. 2002/0067666). Specifically, Maeda was relied upon for teaching the features of dependent claim 22 (e.g., multiple recording layers), which were admittedly lacking from Lee and Eguchi.

However, it is respectfully submitted that Maeda does not disclose or suggest the above-discussed features of independent claim 44 which are lacking from Lee and Eguchi. Therefore, no obvious combination of Lee, Eguchi and/or Maeda would result in, or otherwise render obvious, the invention recited independent claim 44 and claim 45 that depends therefrom.

## V. CONCLUSION

In view of the above amendments and remarks, it is submitted that the present application is now in condition for allowance and an early notification thereof is earnestly requested. The Examiner is invited to contact the undersigned by telephone to resolve any remaining issues.

Respectfully submitted,

Shinya ABE et al.

/Andrew L. Dunlap/

By: 2008.07.29 14:03:03 -04'00'

Andrew L. Dunlap  
Registration No. 60,554  
Attorney for Applicants

ALD/led  
Washington, D.C. 20006-1021  
Telephone (202) 721-8200  
Facsimile (202) 721-8250  
July 29, 2008

## DESCRIPTION

~~WOBBLE INFORMATION RECORDING METHOD, INFORMATION RECORDING MEDIUM,  
AND RECORDING AND REPRODUCTION METHOD AND APPARATUS THEREOF~~

INFORMATION RECORDING MEDIUM AND  
INFORMATION REPRODUCING METHOD

BACKGROUND OF THE INVENTION

~~TECHNICAL FIELD~~

1. FIELD OF THE INVENTION

The present invention is related to a method for recording wobble information of an information recording medium such as an optical disk so that a polarity of detected wobble information is the same irrespective of the recording system, and an information recording medium wherein the wobble information is recorded according to the method. Further, the present invention is related to a method and apparatus for recording and reproducing information using the information recording medium.

~~BACKGROUND OF THE INVENTION~~

2. DESCRIPTION OF THE RELATED ART

Conventionally, CD-R/RW ~~or~~ and DVD-R/RW/RAM have been used as a write-once or ~~an~~ a rewritable optical disk and recently demand for a DVD-R/RW/RAM has been increased since



~~a~~ DVD recorders ~~has~~ have widely prevailed for recording TV broadcasts. A guide groove is provided in these optical disks and reference signals for synchronizing a linear velocity upon recording and reproducing and optional address information signals are recorded in these optical disks by "wobble" signals which are a meander of the guide groove. A recording and reproduction apparatus for such an optical disk records and reproduces information by detecting the wobble signals to adjust the linear velocity and by detecting the address if the address information is added to the optical disk. Of the above optical disks, the DVD-RAM employs a recording system (or a recording mode) which may be called as a "land & groove" recording system according to which recording and reproduction of information are carried out on both ~~of~~ land portions (that are faces far from a light used for recording and reproduction) and the groove portions (that are faces near to the light) of the guide groove, and all the other optical disks employ a groove recording system according to which the recording and reproduction of information are carried out only on the groove portions (that are faces near to the light used for recording and reproduction) of the guide groove.

Recently, an optical disk ~~whose~~ having a recording density that is higher than the DVD has been developed. In

general, information is recorded on and reproduced from the optical disk by an incident light for recording and reproduction which light passes through a transparent layer which may be called ~~as~~ a "substrate." The thickness of the substrate, through which the light for recording and reproduction passes, is 0.6 mm for the DVD. ~~The~~ A study has been made for further thinning the thickness of the substrate into about 0.1 mm and thereby using a light with a short wavelength for recording and reproduction. As a result, a recordable Blu-ray Disc (BD) has been developed.

In the case where the thickness of the substrate is thin such as 0.1 mm, it is difficult to form the guide groove in the sheet having a thickness of 0.1 mm and to form the recording layer on its surface. For this reason, an approach for producing the Blu-ray Disc is made wherein the guide groove is formed in a substrate of a 1.1 mm thickness which is to be positioned at the side (rear side) that is not irradiated with the light for recording and reproducing and the recording layer is formed on the guide groove followed by forming a cover layer of a 0.1 mm thickness. In this case, the light for recording and reproducing is applied from the side of the cover layer.

When the recording layer is formed by sputtering a material ~~for~~ forming the recording layer onto the surface of the rear-side substrate, the recording layer can be

deposited and formed so that the thickness of the recording layer in the groove portions (the top surface of the guide groove) is almost the same as that in the land portions (the bottom surface of the guide groove) viewed from the cover layer side where the light for recording and reproducing is applied. Therefore, in this case, the portions that present a better recording and reproduction characteristics, which is generally the groove portions, can be used for recording and reproduction.

Further, there is a method for applying an organic dye by a spin-coat method, as a method for forming the recording layer. For example, Japanese Patent Kokai (Laid-Open) Publication No. 2003-109246(A) describes a method for producing a write-once optical disk which includes forming the recording layer by applying the organic dye on the rear-side substrate by the spin-coat method and then forming the cover layer. However, according to the spin coat method, the organic dye preferentially deposits in the groove portions (concaved portions) of the substrate. As a result, the recording layer is formed thickly in the land portions when viewed from the cover layer side. Therefore, since the recording film is easily formed in the land portions in this case, it is preferable that the land portions are used for recording and reproduction.

BRIEF SUMMARY OF THE INVENTION

As described above, an appropriate recording system depends on the method for forming the recording film. However, when tracking is conducted by, for example, a push-pull method, tracking characteristics obtained when using the groove portions as the recording layer is reversal of those when using the land portion as the recording layer. Similarly, a polarity of wobble signals obtained in reproduced signals when reproducing the signals recorded in the groove portions is reversal of a polarity of wobble signals obtained in reproduced signals when reproducing the signals recorded in the land portions.

In a recording and reproduction apparatus, a circuit for tracking is generally separated from a circuit for detecting wobble signals. For this reason, when it is desired that a single recording and reproduction apparatus accepts two types of optical disks, one being of the groove recording system, and the other being of the land-recording system, it is necessary to (i) detect whether the portions to be used for recording ~~is the~~ are groove portions or ~~the~~ land portions and ~~to~~ (ii) detect the wobble signal polarity for a loaded optical disk, which results in a problem that a longer time is required for start-up.

In order to resolve this problem, the present inventors propose that the polarity obtained upon

reproducing the wobble signals is made the same in both of the information recording medium of a land-recording system and the information recording medium of a groove-recording system. Specifically, the polarity of wobble signals formed in the optical recording medium, which employs one recording system, is made mirror reverse of that formed in the optical recording medium which employs the other recording system. More specifically, the physical direction of the wobble (specifically, right and left of starting direction of the wobble, that is, whether the wobble starts its first wobble deviation towards the inner side or the outer side of the medium), in the case of the groove-recording system, is reversed ~~in the wobble~~ in the case of the land-recording system so that the polarity of the wobble signals in the case of the land-recording system is made to be the same as the polarity of the wobble signals in the case of the groove-recording system. Herein, the phrase "the wobble starts its first wobble deviation towards the inner side of a medium" means that a starting point of the wobble is positioned at the innermost of the medium (a position nearer to the center in the case of a disk) relative to a position where a wobble amplitude is zero and the wobble starts from the starting point as shown in Fig. 6. The phrase "the wobble starts its first wobble deviation towards the outer side of a medium" means that a

starting point of the wobble is positioned at the outermost of the medium relative to a position where the wobble amplitude is zero and the wobble starts from the starting point as shown in Fig. 7. Both ~~of the~~ wobbles shown in  
5 Figs. 6 and 7 are monotone wobbles. Timing and address information by MSK (Minimum Shift Keying) modulation and HMW (Harmonic Modulated Wave) modulation are optionally incorporated into the monotone wobble.

Thus, the present invention provides a method for  
10 recording wobble information of an information recording medium which includes:

selecting a recording system; and

forming a guide groove having wobble information wherein the wobble starts its first wobble deviation  
15 towards the inner side of the medium in the case where the selected recording system is a groove-recording system, or a guide groove having wobble information wherein the wobble starts its first wobble deviation towards the outer side of the medium in the case where the selected recording system  
20 is a land-recording system. This is particularly applicable to an optical disk on and from which information is recorded and reproduced with a light. This method makes it possible that the polarity of the wobble signals of the  
information recording medium of a ~~the~~ groove-recording  
25 system is the same as that of the information recording

medium of the land-recording system. According to this method, an information recording medium of groove-recording system, wherein a wobble starts its first wobble deviation towards the inner side of the medium in a guide groove having wobble information, and an information recording medium of land-recording system, wherein a wobble starts its first wobble deviation towards the outer side of the medium in a guide groove having wobble information can be obtained.

Further, the present invention provides a method for recording wobble information of a multi-layer information recording medium having a plurality of recording layers, which includes making the wobble polarity that is detected from all the recording layers to be the same, and a multi-layer information recording medium having a plurality of recording layers wherein wobble information is recorded according to this method. In such an information recording medium, the wobble starts its first wobble deviation towards the inner side or the outer side of the medium in a guide groove having wobble information for each recording layer depending on a recording system of ~~the~~ each recording layer. Herein, the terms "a guide groove for a certain recording layer" means a groove for guiding a light used for recording information on the certain recording layer and reproducing the information from the certain recording

layer.

Furthermore, the present invention provides a method for recording information on and reproducing information from an information recording medium of the present invention, which includes judging a tracking polarity peculiar to a loaded information recording medium (particularly, an optical disk), based on the result of whether or not wobble information is detected from wobble signals under a fixed tracking polarity. Further, the present invention provides a recording and reproduction apparatus which is used for carrying out this method.

In ~~these~~ the above-mentioned recording and reproduction method and apparatus, the default of the tracking polarity may be preferably one for a groove-recording system. Since many optical disks conventionally employ the groove-recording system, it may be considered that many unspecified optical disks also employ the groove-recording system. For this reason, the default of the tracking polarity is one for the groove-recording system and a detection time required for detecting an optical disk of the groove-recording system can be ~~shorten~~ shortened, whereby the start time when the unspecified optical disk is loaded can be shortened.

This invention makes it possible to omit the time required for a recording and reproduction apparatus to



study the wobble polarity of each optical disk, irrespective whether its recording system is the groove-recording system or the land recording system. Further, the recording system of the information recording medium of the present invention can be easily judged by detecting whether or not the wobble information is obtained from the wobble signals when tracking is carried out under a predetermined polarity.

#### 10 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic view of an optical disk according to a first embodiment of the present invention;

Fig. 2 is a schematic view of a laser master recording apparatus for producing a master of the optical disk according to the first embodiment of the present invention;

Fig. 3 is a block diagram of a signal reproduction circuit of the optical disk according to the first embodiment of the present invention;

Fig. 4 is a schematic view describing a groove polarity and a tracking signal polarity of the optical disk according to the first embodiment of the present invention;

Fig. 5 is a schematic view of an optical disk according to a second embodiment of the present invention;

Fig. 6 is a schematic view showing an example of wobble of a guide groove formed in an information recording

medium of groove-recording system, according to a method of the present invention; and

Fig. 7 is a schematic view showing an example of wobble of a guide groove formed in an information recording medium of land-recording system, according to a method of the present invention.

Here, in Figs. 1 to 7, the reference numbers represent the following elements:

101...substrate, 102...recording film, 103...overcoat,  
 10 104...UV curable resin layer, 105...PC sheet, 201...laser,  
 202...light regulator, 203...deflector, 204...beam expander,  
 205...movable optical bench, 206... master, 207,  
 208...mirror, 209...formatter, 210...objective lens,  
 301...optical disk, 302...objective lens, 303...mirror,  
 15 304...photodetector, 305, 306... preamplifiers, 307...  
 differential amplifier, 308...tracking circuit,  
 309...wobble detecting circuit, 501...substrate,  
 502...second recording film, 503...intermediate layer,  
 504...first recording film, 505...UV curable resin layer,  
 20 and 506...PC sheet.

#### ~~DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS~~

#### DETAILED DESCRIPTION OF THE INVENTION

The embodiments of the present invention are described with reference to the attached drawings.

(First Embodiment)

Fig. 1 shows a schematic view showing a construction of an optical disk according to the first embodiment of the present invention. The optical disk includes a substrate 101, a recording film 102 formed on a surface of the substrate 101, an overcoat layer 103 formed on a surface of the recording film 102 and a sheet 105 bonded to the overcoat layer 103 through an adhesive layer 104. The substrate 101 is a substrate (or plate) which is formed by injection molding and has a guide groove wherein wobble information is recorded on its surface where the recording film 102 is formed. The substrate 101 has a thickness of about 1.1 mm. The recording film 102 may be formed by, for example, a spin coat method using an organic dye. The overcoat layer 103 may be formed ~~of~~ from a UV curable resin into a thickness of about 4  $\mu$ m. The sheet 105 may be a polycarbonate sheet (PC sheet) having a thickness of about 80  $\mu$ m, and it may be bonded to the overcoat layer 103 by the adhesive layer 104 of a UV curable layer.

A stamper ~~gives~~ provides the guide groove on the substrate upon the injection molding. That is, the stamper corresponds to a mold of the guide groove. The stamper may be produced using a master that is produced using a laser master recording apparatus.

Fig. 2 is a schematic view showing a construction of the laser master recording apparatus. A light emitted from a light source that is a laser 201 (whose wavelength is 248 nm) is reflected on a mirror 207 and its intensity is adjusted in a light regulator 202. The light is further reflected on a mirror 208 and deflected by a deflector 203. At this moment, wobble information to be recorded is generated in a formatter 209 and introduced in the deflector 203. The diameter of the light deflected by the deflector is adjusted in a beam expander 204, focused by an objective lens 210 that is mounted in a movable optical bench 205, and applied to a master 206. A photoresist has been applied to the surface of the master 206 which is irradiated with the light. The master 206 is rotated on a spindle.

By changing the output polarity of the formatter 209, it is possible to change the physical direction of the wobble recorded in the master 206, that is, the direction of the first wobble deviation (that is, whether the wobble starts its first wobble deviation towards the inner side or the outer side of the disk). Therefore, the method for recording wobble information of the present invention can be carried out by determining the recording system of the optical disk to be produced, selecting the output polarity of the formatter based on the determination, and producing

the master by means of this master recording apparatus, and producing the stamper from this master, and forming the guide groove in the surface of the substrate using this stamper.

5           In addition to reference frequency information which  
| ~~are~~is used in order that a recording and reproduction  
apparatus synchronizes a linear velocity, address  
information may be added to the wobble information by  
mixing signals (STW; Saw Tooth Wobbles) that are added  
10 | while advancing or delaying the phase of a wave having a  
double frequency relative to the reference frequency and  
signals having 1.5 times frequency of the reference  
frequency (MSK; Minimum Shift Keying).

          In general, a Blu-ray Disc employs the groove-  
15 recording system. In that case, the wobble starts its  
first wobble towards the inner side of the medium, that is,  
the wobble starts at the inner side of the medium. In  
other words, the wobble starts at a point where the wobble  
amount (or an amplitude) is maximum on the inner side of  
20 the medium. Such a wobble is as shown in Fig. 6. As shown  
in Fig. 6, in the case of the groove-recording system, the  
starting point of the wobble is situated at the inner side  
of the medium.

          In the first embodiment, the output characteristic of  
25 the formatter 209 is set so that the wobble starts its

first wobble deviation towards the outer side of the disk, that is, the wobble starts at the outer side of the disk, considering that this disk employs the land-recording system. In other words, the output characteristic of the  
5 formatter 209 is set so that the wobble starts at a point where the wobble amount is at a maximum on the outer side of the disk. The wobble employed in the optical disk of land-recording system is as shown in Fig. 7, and the start point of the wobble is situated at the outer side of the  
10 disk.

Fig. 3 shows a block diagram for detecting tracking signals and wobble signals in a recording and reproduction apparatus at the time of recording information on and reproducing information from a fabricated optical disk. As  
15 shown in Fig. 3, a light reflected on an optical disk 301 is focused by an objective lens 302 and reflected on a mirror 303 and then introduced in a bisected photodetector 304. The section (or dividing) line is disposed perpendicular to movement of a radial direction of the  
20 optical disk.

Outputs of channels of the photodetector 304 are amplified by preamplifiers 305 and 306 respectively, become a differential signal in a differential amplifier 307, and the differential signal is input into a tracking circuit  
25 308 and an address detecting circuit 309.

Fig. 4 shows the relationship between push-pull tracking error signals corresponding to the groove portions (G) and the land portions (L) when a spot of the light used for recording and reproduction traverses the guide groove.

5 As shown in Fig. 4, the tracking error signals change as a substantially sinusoidal waveform depending the period of the guide groove. Although the error signals become zero at the center of the groove portion and at the center of the land portion, the inclination at the groove center is  
10 opposite to the inclination at the land center. The reproduced wobble signals are generated by sifting the groove or the land purposefully and its polarity is the same as that of the tracking error signals.

Therefore, in the case where a conventional master for  
15 an optical disk of land-recording system is used to produce an optical disk by, for example, a mothering method so that a predetermined information is recorded in land portions and the optical disk is used as one of land-recording system, the polarity of the reproduced wobble signals is  
20 reversed. In the first embodiment, the wobble recording polarity is opposite to that employed in a medium of groove-recording system. For this reason, even if the tracking polarity is adapted to the land portion, the wobble signals whose polarity is opposite to the tracking  
25 polarity are obtained. As a result, the polarity of

reproduced wobble signals from the optical disk of the first embodiment becomes identical with the polarity of those from the optical disk of groove-recording system.

~~In lieu of the present invention~~If the wobble does not  
5 start a first wobble deviation toward the outer side of the  
optical disk of the land-recording system, it might be  
~~considered that~~ a method for reversing both ~~of~~ the wobble-  
signal polarity and the tracking-signal polarity for a  
groove-recording system, by means of a common amplifier in  
10 a recording and reproduction apparatus, should be  
considered when recording information on and reproducing  
information from the optical disk. ~~of land-recording system.~~

This method does not require that the wobble shape for the  
land-recording system is a reversal of the wobble shape for  
15 the groove-recording system. However, the frequency band  
of the wobble signals is significantly different from that  
of the tracking error signals (the former is several kHz  
and the latter is several tens of kHz), a mechanism wherein  
the wobble signal and the tracking error signal are  
20 separately managed using respective circuits designed  
specifically for respective signals has an advantage that  
the property of the recording and reproduction apparatus is  
maintained more easily compared to a mechanism which  
reverses the polarities using the common amplifier. In the  
25 following, a method and an apparatus for recording



information in and reproducing information from an optical disk wherein the wobble information is recorded according to the method of the present invention.

5 The optical disk recording and reproduction apparatus of the present invention is used with its tracking polarity set for a groove-recording system and a land-recording system, preferably for the groove-recording system. When a conventional optical disk of groove-recording system is loaded in the recording and reproduction apparatus, wherein  
10 the tracking polarity is set for the groove-recording system and tracking is carried out with an appropriate mechanism, wobble information is detected from wobble signals. The detected information during this tracking may be—preferably address information included in the wobble  
15 information or another characteristic information from which a location on the disk can be identified. In the case of an optical disk of CLV (Constant Linear Velocity), the reference frequency signal may be detected as the wobble information. When the wobble information is  
20 detected by setting the tracking polarity for the groove-recording system, the loaded optical disk is identified as one of groove-recording system. When the wobble information is not detected, the tracking polarity is switched and the detection of wobble information is carried  
25 out again. After switching, when the wobble information is

detected, the loaded optical disk can be identified as one  
of a land-recording system.

The optical disk of the first embodiment can be  
identified as ~~one—being of—a~~ land-recording system  
5 according to the latter procedure.

As described above, the number of combinations of the  
tracking polarity and the wobble polarity is reduced by  
always detecting a wobble polarity of an optical disk under  
the same polarity in a recording and reproduction apparatus,  
10 whereby a start-up time is reduced upon loading the optical  
disk.

#### (Second Embodiment)

Fig. 5 is a schematic view showing a construction of  
15 an optical disk of a second embodiment. This disk has two  
recording films. A second recording film 502 which is  
located further from a laser light may be formed on a  
substrate 501 using an organic dye by a spin-coat method.  
The substrate 501 is produced in the same manner as in the  
20 first embodiment. Next, an intermediate layer 503 having a  
guide groove on its surface is stacked. The guide groove  
formed in the intermediate layer 503 is used to record  
information on and reproduce information from a first  
recording film 504 that is located near to the laser light  
25 and it also may be formed using a stamper which is produced

~~with a~~ from a master. The first recording film 504 whose main component may be a Te oxide film may be formed on a surface of the intermediate layer 503 by a sputtering method. A polycarbonate sheet (PC sheet) 506 having a  
5 | thickness of about 65\_μm is bonded to the surface of the second recording film 504 through a UV curable resin layer 505. A method for stacking the intermediate layer 503 is described in Japanese Patent Kokai (Laid-Open) Publication No. 2003-203402(A) that is incorporated herein by reference.

10 | In this optical disk, the recording system of the second recording film 502 is a land-recording system, and the recording system of the first recording film 504 is groove-recording system. Therefore, the wobble guide  
15 | groove is formed so that the ~~wobbles~~ wobble starts its first wobble deviation towards the outer side of the disk, that is, the wobble starts at the outer side of the disk, in the substrate 501 where the second recording film 502 is formed, while the wobble guide groove is formed so that the  
20 | wobble starts its first wobble deviation towards the inner side of the medium, that is, the wobble starts at the inner side of the medium in the intermediate layer 503 for the first recording film 504. Each wobble guide groove for each recording layer is also formed by producing a master that determines the shape of the guide groove with a laser  
25 | master recording apparatus so as to record wobble

information in a predetermined manner, and forming the substrate 501 or the intermediate layer 503 by means of a stamper that is formed by the master.

5 This construction enables a two-layer optical disk to be obtained, wherein the tracking polarities of both recording layers are different from each other, while the detecting polarity of the wobbles of both recording layers are the same.

10 Also for this optical disk, the tracking polarity of each recording layer can be easily identified according to the procedure for distinguishing an optical disk of a groove-recording system from an optical disk of a land-recording system with use of a recording and reproduction apparatus as mentioned above, in a manner as described in  
15 connection with the first embodiment. Therefore, the start-up time is shortened by using ~~this~~ the above-  
mentioned optical disk and ~~a~~ recording and reproduction  
apparatus, which is provided with a mechanism for tracking each recording layer.

20 As the second embodiment, the two-layer optical disk is described which has two recording layers whose recording systems are different from each other. Of course, a similar construction may be applied to an optical disk wherein the recording systems of the first and the second  
25 recording layers are the same. For example, in the case

where the recording systems of the first and the second  
recording layers are both groove-recording systems, the  
guide grooves are formed in the substrate and the  
intermediate layer so that wobbles start their first wobble  
deviation towards the inner side of the medium. Further, a  
similar construction is applicable to a multi-layer optical  
disk having more than two recording layers (for example, an  
optical disk having four recording layers). The optical  
disk having four recording layers has a combination wherein  
land portions or groove portions are used for recording in  
each of the four recording layers. The combination may be,  
for example, a construction wherein groove-groove-groove-  
groove-recording systems are employed in the respective  
layers in this order from the side near to a laser light,  
or a construction wherein groove-groove-groove-land-  
recording systems are employed in the respective layers in  
this order from the side near to a laser light.

In the first embodiment and the second embodiment, the  
physical polarity of the wobble is reversed on the optical  
disk. Alternatively, the polarity of the reproduced wobble  
signals can be reversed by changing a depth of the guide  
groove. To this end, the depth of the guide groove or the  
refractive index of a material for the recording layer may  
be adjusted so that a difference between the optical path  
length of a light reflected on a groove portion and the

optical path length of a light reflected on a land portion is not less than  $\lambda/2$  and not greater than  $\lambda$  ( $\lambda$ : a wavelength of a light used for recording and reproduction).

As described above, by recording wobble information according to the present invention, there is an advantage that detection of the recording system of an optical disk (that is, detecting whether the optical disk employs a groove-recording system or a land-recording system) can be easily made, and therefore the start-up time can be shortened upon loading the optical disk into the recording and reproduction apparatus. The present invention can be applied to various recordable disks, such as a BD-R, a BD-RE, a DVD-R, and a DVD-RW. The present invention may be preferably applicable to the BD-R on and from which information is recorded and reproduced with a laser beam having a wavelength in a blue-violet region (specifically, about 405\_nm).

The method for recording wobble information of the present invention is characterized in that the polarity of wobble information is made to be the same irrespective of the recording system (a groove-recording system or a land-recording system) of an information recording medium. Therefore, the present invention is advantageously applied particularly to an information recording medium as to which both recording systems are allowed (that is, coexisting)

according to a specification (or a standard).

Further, the method and apparatus for recording and reproducing information of the present invention using the optical disk of the present invention employs a specific  
5 procedure and thereby makes it possible to reduce the load on the recording and reproduction apparatus which load is added until the apparatus identifies the recording system of the information recording medium. As a result, the  
recording and reproduction method and apparatus, wherein  
10 the time required for start-up is reduced, can be realized.

## ABSTRACT

An optical disk and a method for identifying the optical disk ~~are provided which make~~ making it possible to identify a recording system of the optical disk easily in a short time by a recording and reproduction apparatus when a groove-recording system and a land-recording system are both employed in one kind of optical disk, such as, for example, ~~for, example,~~ a BD-R. Specifically, ~~the~~ a polarity upon reproducing ~~the~~ wobble information is made to be the same in both ~~of the~~ an optical disk of groove-recording system and the optical disk of a land-recording system. The recording system of the optical disk that shows the same wobble polarity irrespective of the recording system can be easily detected by finding a tracking polarity that can recognize the wobble information by changing the tracking polarity, whereby the start-up time of the recording and reproduction apparatus can be shortened.